


# AIROMAX AM 27

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>385/95 R 25</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | GRÚA MÓVIL   |
| <b>VERSIÓN</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 170 F  |



## DIMENSIONES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94044214 | <b>RIM REC</b> | 10.00/1.5       |
| <b>OD (IN)</b>    | 53.7     | <b>ECE</b>     | E11-54R-0015911 |
| <b>SLR (IN)</b>   | 24.6     |                |                 |
| <b>RC (IN)</b>    | 164.4    |                |                 |

## LOAD CAPACITY (LBS/TIRE)

|                  |            |
|------------------|------------|
| <b>MPH / PSI</b> | <b>130</b> |
| 50               | 13200      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.