

# AS 505

<b>TIRE SIZE</b>	<b>6.5/80 - 15</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	OUTILLAGE AGRICOLE / REMORQUE / OUTILLAGE AGRICOLE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	92 A8
<b>LI/SS FREE ROLLING</b>	104 A8



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94019472	<b>RC (IN)</b>	82.9
<b>SW (IN)</b>	6.7	<b>RIM REC</b>	5.0
<b>OD (IN)</b>	27.4	<b>RIM ALT</b>	4½ K; 5 K; 5 J
<b>SLR (IN)</b>	12.8	<b>ECE</b>	E4-106R-002660

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	70
5 FR	2780
15 FR	2360
20 FR	2230
25 FR	1980
5 DW	1940
15 DW	1650
20 DW	1550
25 DW	1390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.