


AGRIMAX RT 657

| | |
|---------------------|--|
| TIRE SIZE | 600/65 R 28 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | VINEYARD HARVESTER / TRACTOR / HARVESTER |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 154 D ; 157 A8 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 611 | RIM REC | DW 20 B |
| OD (MM) | 1491 | RIM ALT | W 18 L |
| SLR (MM) | 670 | ECE | E4-106R-000621 |
| RC (MM) | 4470 | SRI | 700 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|--------------|------|------|------|------|------|------|------|------|
| 65 | 1800 | 2100 | 2365 | 2625 | 2890 | 3115 | 3450 | 3750 |
| 50 | 1895 | 2210 | 2485 | 2760 | 3035 | 3275 | 3625 | 3940 |
| 40 | 1980 | 2310 | 2600 | 2890 | 3180 | 3425 | 3795 | 4125 |
| 30 | 2075 | 2420 | 2720 | 3025 | 3325 | 3585 | 3970 | 4315 |
| 10 LT | 2415 | 2815 | 3170 | 3520 | 3870 | 4175 | 4625 | 5025 |
| 10 HT | 2075 | 2420 | 2720 | 3025 | 3325 | 3585 | 3970 | 4315 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.