

# TR 171

|                     |               |
|---------------------|---------------|
| <b>TIRE SIZE</b>    | <b>8 - 18</b> |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> | ❖ BIAS        |
| <b>MACHINERY</b>    | TRATOR        |
| <b>VERSÃO</b>       | STANDARD      |
| <b>TIRE TYPE</b>    | TT            |
| <b>LI/SS</b>        | 85 A6         |



## DIMENSÕES IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 190  | <b>RIM REC</b> | W 6             |
| <b>OD (MM)</b>  | 845  | <b>RIM ALT</b> | W 7; 5.50 F     |
| <b>SLR (MM)</b> | 391  | <b>ECE</b>     | E11-106R-003488 |
| <b>RC (MM)</b>  | 2617 | <b>PR</b>      | 4               |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>1.20</b> |
| 30                | 515         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.