


# RIDEMAX FL 693 M



<b>TIRE SIZE</b>	<b>600/50 R 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CISTERNA MÓVEL / REBOQUE / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	159 D ; 156 E

## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94037032	<b>RC (IN)</b>	140.7
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	46.1	<b>ECE</b>	E4-106R-000805
<b>SLR (IN)</b>	20.3		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41	46	52	58
45	3260	3700	4500	5200	6000	6790	7320	8110	8820
40	3570	4060	4930	5700	6560	7430	8010	8870	9640
30	4320	4910	5960	6890	7950	8990	9690	10750	11670
25	4860	5510	6690	7750	8930	10110	10890	12070	13120
15	5640	6400	7780	8990	10370	11740	12650	14030	15240
5	6430	7300	8860	10250	11810	13370	14420	15970	17360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.