

AGRIMAX RT 600

TIRE SIZE	900/60 R 32
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	181 A8 ; 178 B



РАЗМЕРЫ US STANDARD

USA CODE	94062423	RC (IN)	224.3
SW (IN)	35.3	RIM REC	DW 27 B
OD (IN)	74.5	RIM ALT	DW 28 B; DW 30 B
SLR (IN)	33.1	ECE	E11-106R-005768

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	20	23	29	35	41	46	49	55
30	7440	8430	9590	10580	11740	13060	14050	15380	16530	-	-
25	8190	9280	10550	11640	12920	14370	15460	16920	18190	-	-
20	8760	9930	11300	12470	13820	15390	16560	18110	19470	-	-
5 LT	10970	12430	14140	15610	17310	19260	20720	22670	24370	-	-
5 HT	8760	9930	11300	12470	13820	15390	16560	18110	19470	-	-
5 CYC.	-	14910	16950	18710	20760	23090	24840	27180	29220	29680	30920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.