

FLOTATION 648

| | |
|---------------------------|---|
| TIRE SIZE | 800/45 - 26.5 |
| UM | US STANDARD |
| CONSTRUCTION | BIAS |
| MACHINERY | ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 158 A8/155 B |
| LI/SS FREE ROLLING | 170 A8/167 B |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CÓDIGO USA | 94006557 | RC (IN) | 164.8 |
| SW (IN) | 31.5 | RIM REC | AG 28.00 |
| OD (IN) | 54.8 | ECE | E11-106R-004557 |
| SLR (IN) | 24.8 | PR | 12 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 22 | 23 | 25 |
|--------------|-------|-------|-------|
| 5 FR | 17210 | 17870 | 18520 |
| 10 FR | 15490 | 16080 | 16670 |
| 20 FR | 13770 | 14300 | 14810 |
| 25 FR | 12290 | 12760 | 13230 |
| 30 FR | 11070 | 11490 | 12010 |
| 5 DW | 12190 | 12650 | 13120 |
| 10 DW | 10970 | 11390 | 11810 |
| 20 DW | 9750 | 10120 | 10490 |
| 25 DW | 8710 | 9040 | 9370 |
| 30 DW | 7840 | 8130 | 8540 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.