

# FORESTECH

|                     |                      |
|---------------------|----------------------|
| <b>TIRE SIZE</b>    | 750/55 - 26.5        |
| <b>UM</b>           | US STANDARD          |
| <b>CONSTRUCTION</b> | ❖ BIAS               |
| <b>MACHINERY</b>    | FORWARDER / FORESTRY |
| <b>VERSION</b>      | STEEL BELTED         |
| <b>TIRE TYPE</b>    | TL                   |
| <b>LI/SS</b>        | 177 A8 ; 184 A2      |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94031719 | <b>RC (IN)</b> | 175.9           |
| <b>SW (IN)</b>  | 29.7     | <b>RIM REC</b> | AG 24.00        |
| <b>OD (IN)</b>  | 58.5     | <b>ECE</b>     | E11-106R-003347 |
| <b>SLR (IN)</b> | 26.8     | <b>PR</b>      | 20              |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>73</b> |
|------------------|-----------|
| 25               | 16090     |
| 20               | 17220     |
| 5                | 19840     |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.