


RIDEMAX FL 693 M



TIRE SIZE	600/55 R 26.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TANKBIL / SLÄPVAGN / ARBETSFORDON
VERSION	HD
TIRE TYPE	TL
LI/SS	177 D

DIMENSIONER US STANDARD

USA CODE	94049615	RC (IN)	160.5
SW (IN)	24.1	RIM REC	AG 20.00
OD (IN)	52.5	ECE	E11-106R-003007
SLR (IN)	23.1		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41	46	52	58	73	87
45	4990	5960	7240	8380	9660	10950	11750	13040	14330	15130	16090
40	6040	7210	8770	10130	11690	13250	14220	15780	17340	18310	19480
30	6790	8100	9850	11390	13140	14890	15980	17740	19490	20580	21890
25	7540	8990	10950	12640	14580	16530	17750	19700	21640	22850	24300
15	7890	9410	11450	13230	15270	17290	18570	20600	22640	23910	25430
5	8980	10720	13040	15070	17380	19710	21150	23470	25780	27240	28970

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.