

# FLOTATION 648

<b>TIRE SIZE</b>	<b>800/45 - 26.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	164 A8/160 B
<b>LI/SS FREE ROLLING</b>	177 A8/173 B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94006564	<b>RC (IN)</b>	164.8
<b>SW (IN)</b>	31.5	<b>RIM REC</b>	AG 28.00
<b>OD (IN)</b>	54.8	<b>ECE</b>	E4-106R-002280
<b>SLR (IN)</b>	24.8	<b>PR</b>	16

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	26	29	32
<b>5 FR</b>	20030	21310	22530
<b>10 FR</b>	18020	19180	20280
<b>20 FR</b>	16030	17050	18020
<b>25 FR</b>	14310	15220	16090
<b>30 FR</b>	12870	13700	14330
<b>5 DW</b>	13720	14590	15430
<b>10 DW</b>	12350	13140	13890
<b>20 DW</b>	10980	11680	12350
<b>25 DW</b>	9800	10430	11020
<b>30 DW</b>	8820	9380	9920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.