


# AGRIMAX RT 600



<b>TIRE SIZE</b>	<b>1050/50 R 32</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HARVESTER / SPREADER / TRACTOR / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	184 A8 ; 181 B

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94040728	<b>RC (IN)</b>	224.4
<b>SW (IN)</b>	41.7	<b>RIM REC</b>	36.0 VA (multi-piece)
<b>OD (IN)</b>	73.3	<b>ECE</b>	E4-106R-000813
<b>SLR (IN)</b>	32.5		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46	49	55
30	8190	9280	11640	12920	14370	15460	16920	18190	-	-
25	8930	10120	12700	14090	15670	16860	18450	19840	-	-
20	9560	10840	13590	15080	16780	18050	19750	21230	-	-
5 LT	11970	13570	17020	18880	21010	22610	24730	26590	-	-
5 HT	9560	10840	13590	15080	16780	18050	19750	21230	-	-
5 CYC	-	15010	19230	21090	24460	25470	27880	29970	31290	33730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.