


# PL 801

<b>TIRE SIZE</b>	<b>7.50 - 15</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ROTORSCHWADER / ERNTEMASCHINE / GABELSTAPLER / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE / GABELSTAPLER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	220	<b>PR</b>	14
<b>OD (MM)</b>	785		
<b>RIM REC</b>	6.0		
<b>RIM ALT</b>	6.00 S; 6.5		

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>9.30</b>
<b>25 LOAD WHEEL</b>	3640
<b>25 STEER WHEEL</b>	2800
<b>10 OTHER VEHICLES</b>	3640
<b>25 OTHER VEHICLES</b>	2800
<b>STATIC SIDE LOADER</b>	4230

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.