

# AW 702

|                           |                                                                                |
|---------------------------|--------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>          | <b>10.0/80 - 12</b>                                                            |
| <b>UM</b>                 | IS STANDARD                                                                    |
| <b>CONSTRUCTION</b>       | ❖ BIAS                                                                         |
| <b>MACHINERY</b>          | BALER / IMPLEMENT MACHINERY /<br>TRAILER / HARVESTER / IMPLEMENTS<br>/ TRAILER |
| <b>VERSION</b>            | SPECIAL                                                                        |
| <b>TIRE TYPE</b>          | TL                                                                             |
| <b>LI/SS FREE ROLLING</b> | 121 A8                                                                         |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 264  | <b>RIM REC</b> | 9.00            |
| <b>OD (MM)</b>  | 710  | <b>RIM ALT</b> | 7.0             |
| <b>SLR (MM)</b> | 317  | <b>ECE</b>     | E11-106R-004353 |
| <b>RC (MM)</b>  | 2144 | <b>PR</b>      | 10              |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>3.90</b> |
|-------------------|-------------|
| 10 FR             | 2030        |
| 25 FR             | 1725        |
| 30 FR             | 1625        |
| 40 FR             | 1450        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.