

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>420/70 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / TRATOR / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	130 D



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94063024	<b>RC (IN)</b>	144.9
<b>SW (IN)</b>	16.5	<b>RIM REC</b>	W 13
<b>OD (IN)</b>	49.1	<b>RIM ALT</b>	W 12; W 14 L
<b>SLR (IN)</b>	21.8	<b>ECE</b>	E11-106R-005826

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	2300	2690	3060	3440	3810	4190
30	2420	2820	3220	3620	4010	4400
25	2540	2940	3360	3770	4190	4600
20	2660	3090	3530	3960	4390	4820
5 LT	3100	3600	4110	4620	5130	5620
5 HT	2660	3090	3530	3960	4390	4820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.