


AGRIMAX V- FLECTO



TIRE SIZE	VF 710/55 R 34
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR DE ALTA POTENCIA / TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	170 D

DIMENSÕES IS STANDARD

SW (MM)	708	RIM REC	DW 25 B
OD (MM)	1659	RIM ALT	DW 27 B
SLR (MM)	726	ECE	E11-106R-0010831
RC (MM)	4910	SRI	775

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2
70	2675	3110	3600	4040	4475	4910	5460
FROM 65 TO 40	2940	3420	3960	4440	4920	5400	6000
30	2995	3485	4035	4525	5015	5505	6120
20	3055	3555	4115	4615	5115	5615	6240
10	3230	3760	4355	4880	5410	5940	6600
*UPTO 10 CYC WITH FRONT LOADER	4115	4785	5540	6215	6885	7560	8400
10HT	2995	3485	4035	4525	5015	5505	6120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.