

# SKID POWER SK

|                     |                    |
|---------------------|--------------------|
| <b>TIRE SIZE</b>    | <b>10 - 16.5</b>   |
| <b>UM</b>           | IS STANDARD        |
| <b>CONSTRUCTION</b> | ⊠ BIAS             |
| <b>MACHINERY</b>    | CARGADORA COMPACTA |
| <b>VERSIÓN</b>      | STANDARD           |
| <b>TIRE TYPE</b>    | TL                 |
| <b>LI/SS</b>        | 138 A2             |



## DIMENSIONES IS STANDARD

|                 |      |                |      |
|-----------------|------|----------------|------|
| <b>SW (MM)</b>  | 270  | <b>RIM REC</b> | 8.25 |
| <b>OD (MM)</b>  | 775  | <b>PR</b>      | 12   |
| <b>SLR (MM)</b> | 355  |                |      |
| <b>RC (MM)</b>  | 2286 |                |      |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>6.20</b> |
|-------------------|-------------|
| 10                | 2375        |
| 15                | 1875        |
| 25                | 1730        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.