

AGRIMAX RT 600

TIRE SIZE	750/65 R 26
UM	US STANDARD
CONSTRUCTION	
MACHINERY	HARVESTER / SPREADER / TRACTOR / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	171 A8/B



DIMENSIONS US STANDARD

USA CODE	94064311	RC (IN)	196.3
SW (IN)	29.5	RIM REC	DW 24 B
OD (IN)	64.4	RIM ALT	DW 23 B ; DW 25 B
SLR (IN)	29.0	ECE	E11-106R-006182

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	20	23	29	35	41	46	49	55
30	6240	7190	8130	8820	9630	10710	11530	12610	13560	-	-
25	6240	7190	8130	8820	9630	10710	11530	12610	13560	-	-
20	6680	7700	8720	9450	10320	11470	12350	13500	14520	-	-
5 LT	8370	9630	10910	11820	12910	14360	15450	16910	18180	-	-
5 HT	6680	7700	8720	9450	10320	11470	12350	13500	14520	-	-
5 CYC	-	11550	13070	14160	15460	17220	18520	20260	21780	22130	23050

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.