


# MULTIMAX MP 513

<b>TIRE SIZE</b>	<b>365/70 R 18 MPT</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VEICULO UNIVERSAL / CAMIÃO DE FERTILIZANTES / VEICULO UNIVERSAL
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	133 G



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94051366	<b>RC (IN)</b>	116.3
<b>SW (IN)</b>	14.2	<b>RIM REC</b>	11
<b>OD (IN)</b>	38.1	<b>RIM ALT</b>	11 SDC; 12; 12 SDC
<b>SLR (IN)</b>	17.6	<b>ECE</b>	E11-54R-0016138

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	36	44	51	54
55	2380	2820	3350	3880	4410	4540
40	2580	3040	3640	4210	4780	4940
25	2760	3240	3860	4450	5070	5220

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.