


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>520/85 R 46</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IRRORAZIONE / VENDEMMIATRICE / TRATTORE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	173 A8/B



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	516	<b>RIM REC</b>	DW 16 L ; W 16 A ; W 16 L ; DD 16
<b>OD (MM)</b>	2075	<b>RIM ALT</b>	DW 18 L ; W 18 L ; W 18 A
<b>SLR (MM)</b>	964	<b>ECE</b>	E4-106R-001494
<b>RC (MM)</b>	6310	<b>SRI</b>	975

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.4	2.8	3.2	3.6	4.0
<b>50</b>	2340	2720	3105	3485	3870	4250	4875	5330	5785	6175	6500
<b>40</b>	2340	2720	3105	3485	3870	4250	4875	5330	5785	6175	6500
<b>30</b>	2505	2915	3325	3735	4145	4550	5215	5705	6190	6605	6955
<b>10 LT</b>	3135	3645	4160	4670	5185	5695	6535	7140	7750	8275	8710
<b>10 HT</b>	2505	2915	3325	3735	4145	4550	5215	5705	6190	6605	6955

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.