


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>320/65 R 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VINEYARD HARVESTER / TRACTOR / HARVESTER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	109 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	319	<b>RIM REC</b>	W 10
<b>OD (MM)</b>	873	<b>RIM ALT</b>	W 9; W 11
<b>SLR (MM)</b>	392	<b>ECE</b>	E4-106R-000636
<b>RC (MM)</b>	2587	<b>SRI</b>	425

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	600	695	785	870	950	1030
40	600	695	785	870	950	1030
30	645	745	840	930	1020	1105
10 LT	805	930	1055	1165	1275	1385
10 HT	645	745	840	930	1020	1105

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.