

# EARTHMAX SR 46

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 33.00 R 51                                                                               |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | STARRER MULDENKIPPER                                                                     |
| VERSION      | HEAT RESISTANT COMPOUND                                                                  |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 235 B                                                                                    |



## ABMESSUNGEN IS STANDARD

|          |           |             |    |
|----------|-----------|-------------|----|
| OD (MM)  | 3050      | TRA CODE    | E4 |
| SLR (MM) | 1401      | STAR RATING | ★★ |
| RC (MM)  | 9377      |             |    |
| RIM REC  | 24.00/5.0 |             |    |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.00  | 5.25  | 5.50  | 5.75  | 6.00  | 6.25  | 6.50  | 6.75  | 7.00  |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50         | 30000 | 30750 | 32500 | 33500 | 34500 | 35500 | 36500 | 37500 | 38750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.