

# TR 135

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>8.00 - 20</b>   |
| <b>UM</b>        | IS STANDARD        |
| <b>MACHINERY</b> | TRACTOR / ANHÄNGER |
| <b>VERSION</b>   | STANDARD           |
| <b>TIRE TYPE</b> | TT                 |
| <b>LI/SS</b>     | 111 A6             |



## ABMESSUNGEN IS STANDARD

|                 |      |                 |                 |
|-----------------|------|-----------------|-----------------|
| <b>SW (MM)</b>  | 225  | <b>RIM REC</b>  | 5.50 F          |
| <b>OD (MM)</b>  | 965  | <b>ECE</b>      | E11-106R-006959 |
| <b>SLR (MM)</b> | 448  | <b>PR</b>       | 8               |
| <b>RC (MM)</b>  | 2837 | <b>TRA CODE</b> | R1              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.80</b> |
| 30                | 1090        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.