


# AGRIMAX V- FLECTO



<b>TIRE SIZE</b>	<b>VF 710/60 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	173 D

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94069507	<b>RC (IN)</b>	200.7
<b>SW (IN)</b>	27.9	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	67.6	<b>RIM ALT</b>	DW 24 B; DW 27 B
<b>SLR (IN)</b>	29.6	<b>ECE</b>	E11-106R-007201

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	6660	7690	8740	9920	10820	11740	13040
<b>FROM 40 TO 25</b>	7310	8450	9600	10890	11890	12900	14330
20	7460	8630	9800	11110	12140	13160	14620
12	7610	8800	9990	11330	12380	13410	14900
5	8050	9300	10570	11980	13080	14190	15760
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	10240	11840	13450	15260	16650	18050	20060
5 HT	7460	8630	9800	11110	12140	13160	14620

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.