


AGRIMAXFACTOR

| | |
|---------------------|--|
| TIRE SIZE | 520/70 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRAKTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 150 D ; 153 A8 |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 516 | RIM REC | W 16 L |
| OD (MM) | 1749 | RIM ALT | W 15 L; W 18 L |
| SLR (MM) | 795 | ECE | E11-106R-007609 |
| RC (MM) | 5239 | SRI | 825 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 65 | 1845 | 2145 | 2450 | 2750 | 3050 | 3350 |
| 50 | 1940 | 2255 | 2570 | 2890 | 3205 | 3520 |
| 40 | 2020 | 2350 | 2680 | 3010 | 3340 | 3670 |
| 30 | 2125 | 2470 | 2815 | 3165 | 3510 | 3855 |
| 10 LT | 2470 | 2875 | 3280 | 3685 | 4090 | 4490 |
| 10 HT | 2125 | 2470 | 2815 | 3165 | 3510 | 3855 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.