


# AS 504

<b>TIRE SIZE</b>	<b>7.50 - 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELESKOPLADER / FELD-ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / TELESKOPLADER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	103 A8
<b>LI/SS FREE ROLLING</b>	116 A8



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	209	<b>RIM REC</b>	5.50 F
<b>OD (MM)</b>	904	<b>RIM ALT</b>	4.50 E; 6.00 F; 5.00 F
<b>SLR (MM)</b>	422	<b>ECE</b>	E4-106R-002636
<b>RC (MM)</b>	2695	<b>PR</b>	8

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.20
10 FR	1750
25 FR	1490
30 FR	1400
40 FR	1250
10 DW	1225
25 DW	1040
30 DW	980
40 DW	875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.