

# AGRIMAX RT 855

|                  |                                                                                 |
|------------------|---------------------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>380/85 R 28</b>                                                              |
| <b>UM</b>        | IS STANDARD                                                                     |
| <b>MACHINERY</b> | PULVERIZADOR / VENDIMIADORA /<br>TRACTOR / COSECHADORA /<br>MAQUINARIA AGRÍCOLA |
| <b>VERSIÓN</b>   | SPECIAL                                                                         |
| <b>TIRE TYPE</b> | TL                                                                              |
| <b>LI/SS</b>     | 133 A8/B                                                                        |

## DIMENSIONES IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 380  | <b>RIM REC</b> | W 12           |
| <b>OD (MM)</b>  | 1357 | <b>RIM ALT</b> | W 11 ; W 13    |
| <b>SLR (MM)</b> | 606  | <b>ECE</b>     | E4-106R-000597 |
| <b>RC (MM)</b>  | 4015 | <b>SRI</b>     | 650            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|--------------|------|------|------|------|------|------|
| <b>50</b>    | 1135 | 1320 | 1505 | 1690 | 1875 | 2060 |
| <b>40</b>    | 1135 | 1320 | 1505 | 1690 | 1875 | 2060 |
| <b>30</b>    | 1215 | 1415 | 1610 | 1810 | 2010 | 2205 |
| <b>10 LT</b> | 1525 | 1770 | 2020 | 2270 | 2520 | 2765 |
| <b>10 HT</b> | 1215 | 1415 | 1610 | 1810 | 2010 | 2205 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

