

# TR 135

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>13.6 - 28</b>   |
| <b>UM</b>        | IS STANDARD        |
| <b>MACHINERY</b> | TRACTOR / ANHÄNGER |
| <b>VERSION</b>   | HD                 |
| <b>TIRE TYPE</b> | TT                 |
| <b>LI/SS</b>     | 125 A6             |



## ABMESSUNGEN IS STANDARD

|                 |      |                         |                 |
|-----------------|------|-------------------------|-----------------|
| <b>SW (MM)</b>  | 345  | <b>ECE</b>              | E11-106R-004429 |
| <b>OD (MM)</b>  | 1310 | <b>PR</b>               | 8               |
| <b>SLR (MM)</b> | 607  | <b>SRI</b>              | 625             |
| <b>RC (MM)</b>  | 4023 | <b>TRA CODE</b>         | R1              |
| <b>RIM REC</b>  | W 12 | <b>TREAD DEPTH (MM)</b> | 35,5            |
| <b>RIM ALT</b>  | W 11 | <b>TKPH (TK/H)</b>      | 0               |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>2.00</b> |
|-------------------|-------------|
| 30                | 1650        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.