


# AGRIMAX V-FLECTO

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>VF 650/60 R 38</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRATTORE A ELEVATA POTENZA / TRATTORE  |
| <b>VERSIONE</b>     | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 173 D  |



## DIMENSIONI IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 650  | <b>RIM REC</b> | DW 23 B         |
| <b>OD (MM)</b>  | 1745 | <b>RIM ALT</b> | DW 21 B         |
| <b>SLR (MM)</b> | 774  | <b>ECE</b>     | E11-106R-006415 |
| <b>RC (MM)</b>  | 5217 | <b>SRI</b>     | 825             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR                     | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|--------------------------------|------|------|------|------|------|------|------|------|
| 70                             | 2725 | 3135 | 3610 | 4025 | 4500 | 4910 | 5505 | 5915 |
| FROM 65 TO 40                  | 2990 | 3445 | 3965 | 4420 | 4940 | 5395 | 6045 | 6500 |
| 30                             | 3050 | 3515 | 4045 | 4510 | 5040 | 5504 | 6170 | 6630 |
| 20                             | 3110 | 3585 | 4125 | 4600 | 5140 | 5615 | 6290 | 6760 |
| 10                             | 3290 | 3790 | 4365 | 4865 | 5435 | 5935 | 6650 | 7150 |
| *UPTO 10 CYC WITH FRONT LOADER | 4190 | 4825 | 5555 | 6190 | 6920 | 7555 | 8465 | 9100 |
| 10 HT                          | 3050 | 3515 | 4045 | 4510 | 5040 | 5505 | 6170 | 6630 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.