


# EARTHMAX SR 30

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | 20.5 R 25  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | RIGID DUMP TRUCK / LOADER  |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TYRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 193 A2   |



## DIMENSIONS US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>USA CODE</b> | 94075256 | <b>RIM REC</b>     | 17.00/2.0 |
| <b>OD (IN)</b>  | 58.5     | <b>RIM ALT</b>     | 17.00/1.7 |
| <b>SLR (IN)</b> | 26.1     | <b>TRA CODE</b>    | L3        |
| <b>RC (IN)</b>  | 174.8    | <b>STAR RATING</b> | ★★        |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 76    | 80    | 83    | 87    | 91    | 94    |
|-----------|-------|-------|-------|-------|-------|-------|
| 5         | 21500 | 22000 | 22700 | 24000 | 24700 | 25400 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.