

# AGRIMAX RT 765

|                  |                                                                       |
|------------------|-----------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>280/70 R 20</b>                                                    |
| <b>UM</b>        | US STANDARD                                                           |
| <b>MACHINERY</b> | SPRAYER / TRACTOR / VINEYARD<br>HARVESTER / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>   | STANDARD                                                              |
| <b>TL/TT</b>     | TL                                                                    |
| <b>LI/SS</b>     | 116 A8/B                                                              |



## DIMENSIONS US STANDARD

|                 |          |                |               |
|-----------------|----------|----------------|---------------|
| <b>USA CODE</b> | 94021970 | <b>RC (IN)</b> | 106.5         |
| <b>SW (IN)</b>  | 10.8     | <b>RIM REC</b> | W 9           |
| <b>OD (IN)</b>  | 35.4     | <b>RIM ALT</b> | W 8 ; W 10    |
| <b>SLR (IN)</b> | 16.1     | <b>ECE</b>     | E4-106R-00641 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35   |
|-------------|------|------|------|------|------|------|------|------|
| <b>30</b>   | 1300 | 1490 | 1710 | 1930 | 2150 | 2370 | 2570 | 2760 |
| <b>25</b>   | 1300 | 1490 | 1710 | 1930 | 2150 | 2370 | 2570 | 2760 |
| <b>20</b>   | 1390 | 1600 | 1840 | 2070 | 2310 | 2550 | 2760 | 2950 |
| <b>5 LT</b> | 1740 | 2000 | 2290 | 2590 | 2890 | 3190 | 3440 | 3690 |
| <b>5 HT</b> | 1390 | 1600 | 1840 | 2070 | 2310 | 2550 | 2760 | 2950 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.