

TR 882

TIRE SIZE	400/60 - 15.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
VERSION	ARAMID BELTED
TIRE TYPE	TL
LI/SS DRIVE WHEEL	132 A8
LI/SS FREE ROLLING	145 A8



РАЗМЕРЫ US STANDARD

USA CODE	94030101	RC (IN)	102.6
SW (IN)	15.7	RIM REC	AG 13.00
OD (IN)	34.4	ECE	E11-106R-004331
SLR (IN)	14.9	PR	14

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	52
5 FR	8950
15 FR	7610
20 FR	7160
25 FR	6390
5 DW	6170
15 DW	5250
20 DW	4940
25 DW	4410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.