


# TR 171

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>14.9 - 24</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRACTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 124 A8   |



## ABMESSUNGEN US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA-CODE</b> | 94028351 | <b>RC (IN)</b> | 149.3          |
| <b>SW (IN)</b>  | 15.4     | <b>RIM REC</b> | W 13           |
| <b>OD (IN)</b>  | 49.8     | <b>RIM ALT</b> | W 11; W 12     |
| <b>SLR (IN)</b> | 22.6     | <b>ECE</b>     | E4-106R-002742 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>26</b> |
| 25               | 3520      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.