


# RT 747 AGRO INDUSTRIAL

<b>TIRE SIZE</b>	<b>460/70 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	KOMPAKTLADER / TELESKOPLADER / KOMPAKTLADER / TELESKOPLADER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	152 A8/B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94016815	<b>RC (IN)</b>	151.2
<b>SW (IN)</b>	18.3	<b>RIM REC</b>	DW 15 L
<b>OD (IN)</b>	49.4	<b>RIM ALT</b>	DW 14 L ; DW 16 L
<b>SLR (IN)</b>	21.9	<b>ECE</b>	E11-106R-004071

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46
30	3680	4540	5320	6180	6970	7830
25	3680	4540	5320	6180	6970	7830
20	3940	4860	5700	6610	7450	8380
15	4080	5040	5910	6870	7730	8690
5 CYC	5520	6810	7980	9270	10450	11740
STATIC	7730	9530	11180	12980	14630	16430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.