DATA SHEET

PRINTED ON
23-04-2026

AGRIMAX RT 765

	620/70 R 38
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	ILAÇLAMA / TRAKTÖR / ÜZÜM HASAT MAKINESI / BIÇERDÖVER / UYGULAMALI MAKINE
VERSION	SPECIAL
TIRE TYPE	TL
	170 D

UNDEFINED IS STANDARD

SW (MM)	625	**RIM REC**	DW 20 B
OD (MM)	1833	**RIM ALT**	DW 18 L; W 18 L
SLR (MM)	828	**ECE**	E11-106R-005997
RC (MM)	5591	**SRI**	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
65	2340	2760	3180	3540	3960	4320	4740	5100	5580	6000
50	2460	2900	3340	3720	4160	4540	4980	5355	5860	6300
40	2565	3025	3485	3880	4340	4735	5195	5585	6155	6570
30	2695	3175	3660	4075	4555	4970	5455	5865	6420	6900
10 LT	3140	3700	4265	4745	5310	5790	6355	6835	7480	8040
10 HT	2695	3175	3660	4075	4555	4970	5455	5865	6420	6900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..