


AGRIMAX TURF RT 333

TIRE SIZE	240/70 R 16
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	VENDIMIADORA / MAQUINA PARA LA RECOGIDA DE FRUTA / MINITRACTOR / TRACTOR / COSECHADORA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	104 A8/B



DIMENSIONES US STANDARD

CÓDIGO USA	94070282	RC (IN)	87.1
SW (IN)	9.6	RIM REC	W8
OD (IN)	29.2	RIM ALT	W 8 L; W 9
SLR (IN)	13.4	ECE	E11-106R-007531

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	940	1090	1240	1390	1560	1710	1880	1990
25	940	1090	1240	1390	1560	1710	1880	1990
20	1010	1160	1330	1500	1670	1830	2010	2130
5 LT	1260	1450	1670	1880	2090	2310	2520	2670
5 HT	1010	1160	1330	1500	1670	1830	2010	2130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.