

# CON STAR

<b>TIRE SIZE</b>	<b>380/75 - 20</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	INDUSTRIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	148 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94051519	<b>RC (IN)</b>	128.9
<b>SW (IN)</b>	15.2	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	42.5	<b>RIM ALT</b>	W 11; 12 SDC; 12; W 13; 13 SDC; 13
<b>SLR (IN)</b>	19.7	<b>ECE</b>	E11-106R-003022

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>58</b>
25	6940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.