


# AGRIMAXFACTOR

<b>TYRE SIZE</b>	<b>620/70 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	160 D ; 163 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94073610	<b>RC (IN)</b>	227.8
<b>SW (IN)</b>	24.6	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	76.2	<b>RIM ALT</b>	DW18L; W18L
<b>SLR (IN)</b>	34.0	<b>ECE</b>	E11-106R-007764

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23
40	5460	6350	7240	8130	9030	9920
30	5730	6670	7610	8540	9480	10420
25	5990	6970	7940	8920	9900	10870
20	6280	7310	8330	9360	10380	11410
5 LT	7320	8510	9710	10900	12100	13290
5 HT	6280	7310	8330	9360	10380	11410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.