

# AS 504

<b>TIRE SIZE</b>	<b>24X8.50 - 12</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	TELESKOPLASTARE / ÅKERSLÄP / ARBETSFORDON / TELESKOPLASTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	81 A8
<b>LI/SS FREE ROLLING</b>	94 A8



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	216	<b>RIM REC</b>	7 JA; 7.00 I
<b>OD (MM)</b>	610	<b>ECE</b>	E11-106R-0010452
<b>SLR (MM)</b>	284	<b>PR</b>	6
<b>RC (MM)</b>	1761		

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>2.30</b>
10 FR	940
25 FR	795
30 FR	750
40 FR	670
10 DW	645
25 DW	550
30 DW	515
40 DW	462

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.