

# EARTHMAX SR 35

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 775/65 R 29  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | БУЛЬДОЗЕР / ПОГРУЗЧИК /<br>ШАРНИРНО-СОЧЛЕНЕННЫЙ<br>САМОСВАЛ                              |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 195 B ; 206 A2   |



## РАЗМЕРЫ US STANDARD

|                 |          |                    |                      |
|-----------------|----------|--------------------|----------------------|
| <b>USA CODE</b> | 94064410 | <b>RIM REC</b>     | 24.00/3.5            |
| <b>OD (IN)</b>  | 69.0     | <b>RIM ALT</b>     | 24.00/3.0; 25.00/3.5 |
| <b>SLR (IN)</b> | 31.0     | <b>TRA CODE</b>    | E3/L3                |
| <b>RC (IN)</b>  | 209.1    | <b>STAR RATING</b> | ★★/★                 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58    | 62    | 65    | 69    |
|-----------|-------|-------|-------|-------|
| 30        | 24000 | 24700 | 26000 | 26800 |
| 5         | 33100 | 34200 | 36400 | 37500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.