

# ROCK GRIP E4

|                     |                   |
|---------------------|-------------------|
| <b>TIRE SIZE</b>    | <b>24.00 - 49</b> |
| <b>UM</b>           | US STANDARD       |
| <b>CONSTRUCTION</b> | ⊠ BIAS            |
| <b>MACHINERY</b>    | TOMBEREAU RIGIDE  |
| <b>VERSION</b>      | STANDARD          |
| <b>TIRE TYPE</b>    | TL                |



## DIMENSIONS US STANDARD

|                 |          |                 |           |
|-----------------|----------|-----------------|-----------|
| <b>CODE USA</b> | 94026548 | <b>RIM REC</b>  | 17.00/3.5 |
| <b>OD (IN)</b>  | 99.6     | <b>PR</b>       | 42        |
| <b>SLR (IN)</b> | 46.6     | <b>TRA CODE</b> | E4        |
| <b>RC (IN)</b>  | 295.2    |                 |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 83    | 109   |
|-----------|-------|-------|
| 30        | 45400 | -     |
| 5         | -     | 76000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.