

## RT 851

|                  |                    |
|------------------|--------------------|
| <b>TYRE SIZE</b> | <b>14.9 L R 20</b> |
| <b>UM</b>        | US STANDARD        |
| <b>MACHINERY</b> | TRACTOR            |
| <b>VERSION</b>   | STANDARD           |
| <b>TL/TT</b>     | TL                 |
| <b>LI/SS</b>     | 119 A8/B           |



### DIMENSIONS US STANDARD

|                 |          |                |                  |
|-----------------|----------|----------------|------------------|
| <b>USA CODE</b> | 94048632 | <b>RC (IN)</b> | 129.4            |
| <b>SW (IN)</b>  | 14.9     | <b>RIM REC</b> | W 13             |
| <b>OD (IN)</b>  | 43.3     | <b>RIM ALT</b> | W 11; W 12; W 14 |
| <b>SLR (IN)</b> | 19.6     | <b>ECE</b>     | E11-106R-002989  |

### LOAD CAPACITY (LBS/TYRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>30</b>   | 1650 | 1930 | 2190 | 2470 | 2730 | 3000 |
| <b>25</b>   | 1650 | 1930 | 2190 | 2470 | 2730 | 3000 |
| <b>20</b>   | 1770 | 2060 | 2360 | 2650 | 2930 | 3220 |
| <b>5 LT</b> | 2220 | 2580 | 2940 | 3310 | 3670 | 4020 |
| <b>5 HT</b> | 1770 | 2060 | 2360 | 2650 | 2930 | 3220 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.