


# FL 630 SUPER

<b>TIRE SIZE</b>	<b>850/50 R 30.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPARGITORE / AUTOBOTTE / RIMORCHIO / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	182 D



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94073191	<b>RC (IN)</b>	192.7
<b>SW (IN)</b>	33.9	<b>RIM REC</b>	AG 28.00
<b>OD (IN)</b>	64.0	<b>ECE</b>	E11-106R-008232
<b>SLR (IN)</b>	28.4		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46	52	58
45	7000	8700	9900	11430	12960	14160	15520	17050
40	7680	9560	10870	12550	14240	15550	17050	18740
30	9300	11570	13160	15200	17240	18830	20630	22670
25	10450	13010	14780	17080	19380	21150	23190	25480
15	12150	15100	17170	19840	22510	24580	26950	29610
5	13830	17210	19560	22610	25640	28000	30700	33730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.