


# AGRIMAX RT 600

<b>TIRE SIZE</b>	<b>650/65 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOISSONNEUSE / ÉPANDEUR / TRACTEUR / OUTILLAGE AGRICOLE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	157 D ; 160 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	645	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1811	<b>ECE</b>	E11-106R-002990
<b>SLR (MM)</b>	833	<b>SRI</b>	875
<b>RC (MM)</b>	5443		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	2310	2725	3095	3465	3795	4125
50	2430	2865	3255	3645	3990	4335
40	2520	2970	3375	3780	4140	4500
30	2660	3135	3560	3990	4370	4745
10 LT	3100	3650	4150	4650	5090	5530
10 HT	2660	3135	3560	3990	4370	4745

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.