

# AGRIMAX RT 855

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>380/85 R 28</b>  |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> |   |
| <b>MACHINERY</b>    | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>      | STANDARD  |
| <b>TL/TT</b>        | TL  |
| <b>LI/SS</b>        | 133 A8/B  |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 380  | <b>RIM REC</b> | W 12           |
| <b>OD (MM)</b>  | 1357 | <b>RIM ALT</b> | W 11 ; W 13    |
| <b>SLR (MM)</b> | 606  | <b>ECE</b>     | E4-106R-000597 |
| <b>RC (MM)</b>  | 4015 | <b>SRI</b>     | 650            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 50         | 1135 | 1320 | 1505 | 1690 | 1875 | 2060 |
| 40         | 1135 | 1320 | 1505 | 1690 | 1875 | 2060 |
| 30         | 1215 | 1415 | 1610 | 1810 | 2010 | 2205 |
| 10 LT      | 1525 | 1770 | 2020 | 2270 | 2520 | 2765 |
| 10 HT      | 1215 | 1415 | 1610 | 1810 | 2010 | 2205 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.