DATA SHEET

PRINTED ON
22-04-2026

FLOTATION 648

TIRE SIZE	**500/60 - 22.5**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	145 A8/142 B
LI/SS FREE ROLLING	157 A8/154 B

ABMESSUNGEN US STANDARD

USA-CODE	94006342	**RC (IN)**	137.4
SW (IN)	19.7	**RIM REC**	AG 16.00
OD (IN)	46.1	**RIM ALT**	15.00; 17.00
SLR (IN)	20.1	**ECE**	E11-106R-004552

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	29	35
5 FR	9680	11450	12730
10 FR	8710	10310	11460
20 FR	7740	9160	10180
25 FR	6910	8180	9090
30 FR	6220	7360	8270
5 DW	6800	8040	8950
10 DW	6130	7230	8060
20 DW	5450	6440	7160
25 DW	4860	5740	6390
30 DW	4380	5170	5840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..