


AS 504

TIRE SIZE	16.0/70 - 20
UM	US STANDARD
CONSTRUCTION	 BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	135 A8
LI/SS FREE ROLLING	147 A8



РАЗМЕРЫ US STANDARD

USA CODE	94019021	RC (IN)	126.5
SW (IN)	16.5	RIM REC	13
OD (IN)	43.2	RIM ALT	12 SDC; 14; 13 SDC
SLR (IN)	19.2	ECE	E4-106R-001875

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	36
5 FR	9490
15 FR	8070
20 FR	7590
25 FR	6780
5 DW	6720
15 DW	5720
20 DW	5380
25 DW	4810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.