

# EARTHMAX SR 46

|                  |                        |
|------------------|------------------------|
| <b>TIRE SIZE</b> | <b>33.00 R 51</b>      |
| <b>UM</b>        | IS STANDARD            |
| <b>MACHINERY</b> | STEL DUMPER            |
| <b>VERSION</b>   | CUT RESISTANT COMPOUND |
| <b>TIRE TYPE</b> | TL                     |
| <b>LI/SS</b>     | 238 B                  |



## DIMENSIONER IS STANDARD

|                 |           |                         |     |
|-----------------|-----------|-------------------------|-----|
| <b>OW (MM)</b>  | 905       | <b>TRA CODE</b>         | E4  |
| <b>OD (MM)</b>  | 3050      | <b>STAR RATING</b>      | ★★★ |
| <b>SLR (MM)</b> | 1401      | <b>TREAD DEPTH (MM)</b> | 87  |
| <b>RC (MM)</b>  | 9377      | <b>TKPH (TK/H)</b>      | 612 |
| <b>RIM REC</b>  | 24.00/5.0 |                         |     |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 6.00  | 6.25  | 6.50  | 6.75  | 7.00  | 7.25  | 7.50  | 7.75  | 8.00  |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50         | 34500 | 35500 | 36500 | 37500 | 38750 | 40000 | 40000 | 41250 | 42500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.