


# AGRIMAX FORCE

<b>TIRE SIZE</b>	<b>IF 650/85 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN / MOTORSTARK TRAKTOR / TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	179 D



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	663	<b>RIM REC</b>	DW 23 B
<b>OD (MM)</b>	2071	<b>RIM ALT</b>	DW 20 B; DW 21 B
<b>SLR (MM)</b>	927	<b>ECE</b>	E4-106R-002649
<b>RC (MM)</b>	6106	<b>SRI</b>	975

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	3310	3805	4370	4935	5500	6065	6625	7050
<b>FROM 65 TO 40</b>	3640	4185	4805	5425	6045	6665	7285	7750
30	3785	4350	4995	5640	6285	6930	7575	8060
20	3930	4515	5185	5855	6525	7195	7865	8370
10	4620	5310	6100	6885	7675	8460	9250	9840
<b>UPTO 30 CYC</b>	4730	5440	6245	7050	7855	8660	9470	10075
<b>UPTO 15 CYC</b>	5640	6485	7445	8405	9365	10330	11290	12010
<b>UPTO 10 CYC</b>	6185	7110	8165	9220	10275	11330	12380	13175
10 HT	3785	4350	4995	5640	6285	6930	7575	8060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.