


AGRIMAX V-FLECTO



| | |
|---------------------|--|
| TIRE SIZE | VF 620/70 R 42 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MOTORSTARK TRAKTOR / TRAKTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 175 D |

DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 620 | RIM REC | DW 21 B |
| OD (MM) | 1935 | RIM ALT | DW 20 B; DW 23 B |
| SLR (MM) | 849 | ECE | E11-106R-0011233 |
| RC (MM) | 5795 | SRI | 925 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 |
|--------------------------------|------|------|------|------|------|------|------|
| 70 | 3140 | 3640 | 4145 | 4710 | 5210 | 5715 | 6275 |
| FROM 65 TO 40 | 3450 | 4005 | 4555 | 5175 | 5730 | 6280 | 6900 |
| 30 | 3520 | 4085 | 4645 | 5280 | 5840 | 6405 | 7035 |
| 20 | 3590 | 4165 | 4740 | 5385 | 5960 | 6530 | 7175 |
| 10 | 3795 | 4405 | 5010 | 5695 | 6300 | 6910 | 7590 |
| *UPTO 10 CYC WITH FRONT LOADER | 4830 | 5605 | 6380 | 7245 | 8020 | 8795 | 9660 |
| 10HT | 3520 | 4085 | 4645 | 5280 | 5840 | 6405 | 7035 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.