


# AW 711

|                     |                                                                                          |
|---------------------|------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>380/70 R 19.5</b>                                                                     |
| <b>UM</b>           | US STANDARD                                                                              |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | MIETITREBBIA / ATTREZZI AGRICOLI /<br>MIETITREBBIA / ATTREZZI AGRICOLI                   |
| <b>VERSIONE</b>     | STUBBLE RESISTANT                                                                        |
| <b>TIRE TYPE</b>    | TL                                                                                       |
| <b>LI/SS</b>        | 159 A8/B                                                                                 |



## DIMENSIONI US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CODICE USA</b> | 94066605 | <b>RC (IN)</b> | 119.6           |
| <b>SW (IN)</b>    | 15.3     | <b>RIM REC</b> | 11.75           |
| <b>OD (IN)</b>    | 40.1     | <b>RIM ALT</b> | 12.75           |
| <b>SLR (IN)</b>   | 17.5     | <b>ECE</b>     | E11-106R-006808 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12   | 17   | 23   | 29   | 35   | 41   | 46    | 52    | 58    | 73    | 80    |
|-----------|------|------|------|------|------|------|-------|-------|-------|-------|-------|
| 30        | 2850 | 3670 | 4490 | 5170 | 5990 | 6800 | 7290  | 8060  | 8830  | 9070  | 9640  |
| 25        | 2850 | 3670 | 4490 | 5170 | 5990 | 6800 | 7290  | 8060  | 8830  | 9070  | 9640  |
| 20        | 3200 | 4110 | 5030 | 5790 | 6700 | 7620 | 8160  | 9030  | 9890  | 10160 | 10800 |
| 15        | 3390 | 4360 | 5350 | 6150 | 7130 | 8100 | 8670  | 9600  | 10520 | 10800 | 11490 |
| 10        | 3590 | 4630 | 5650 | 6510 | 7540 | 8580 | 9180  | 10160 | 11130 | 11430 | 12160 |
| 5         | 3990 | 5140 | 6280 | 7230 | 8380 | 9520 | 10200 | 11280 | 12360 | 12700 | 13500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.